

Drehschieber-Vakuumpumpen, trockenlaufend

TYP	max. Saugluftmenge [m ³ /h] 50/60Hz	max. Vakuum [mbar abs.] 50/60Hz	max. Vakuum [mbar rel.] 50/60Hz	max. Motorleistung [KW] 50/60Hz
VT 4.2	1,9/2,3	400/400	-600/- 600	0,09/0,105
VT 4.4	4,1/4,7	150/150	-850/- 850	0,18/0,21
VT 4.8	8/9,3	150/150	-850/- 850	0,35/0,42
VT 4.10	10/12	150/150	-850/- 850	0,37/0,45
VT 4.16	16/19	150/150	-850/- 850	0,55/0,77
VT 4.25	25/30	150/150	-850/- 850	0,75/0,90
VT 4.40	40/48	150/150	-850/- 850	1,25/1,50
E V40/V40i	2x40/2x48	100/100	-900/- 900	2,40/3,00
KVT 3.60	55/66	100/100	-900/- 900	2,40/3,00
KVT 3.80	67/78,5	100/100	-900/- 900	2,40/3,00
KVT 3.100	98/112	100/100	-900/- 900	3,00/3,50
KVT 3.140	132/154	100/200	-900/- 800	4,00/4,80
VTLF 200	177/218	200/200	-800/- 800	4,00/4,80
VTLF 250	247/300	200/200	-800/- 800	5,50/6,40

VTLF 360	350/-	250/-	-750/-	11,0/-
VTLF 400	372/450	200/200	-800/- 800	11,0/13,2
VTLF 500	498/600	250/250	-750/- 750	15,0/18,0
VAU VT 4.40/0-400	41	150	-850	1,50
VAU KVT 3.100/0-400	112	100	-900	4,00
VAU VTLF 250/0-400	283	200	-800	7,50